

Please complete this form and email to [info@hennig-inc.com](mailto:info@hennig-inc.com) or fax to your desired location.  
Find your nearest Hennig location.

**COMPANY** *(complete address)*

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Name \_\_\_\_\_

Title \_\_\_\_\_

E-mail \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_ Date \_\_\_\_/\_\_\_\_/\_\_\_\_

**TECHNICAL DATA**

D1 INSIDE spring diameter \_\_\_\_\_

D4 OUTSIDE flange diameter (D1 - 0.40") \_\_\_\_\_

D2 OUTSIDE spring diameter \_\_\_\_\_

D3 INSIDE flange (D2 + 0.80") \_\_\_\_\_

d Maximum screw/rod diameter \_\_\_\_\_

L (max) Fully extended spring length \_\_\_\_\_

L (min) Fully compressed spring length \_\_\_\_\_

Stroke Maximum spring travel \_\_\_\_\_

Orientation  Horizontal  Vertical

**NOTE:**

Flanged collars are not a part of the standard spring assembly, but can be ordered from Hennig. Flanged collars **MUST** allow the spring to rotate during operation. Consult your Hennig Customer Service Rep for the proper flanged collar size and pricing.

**NOTE:**

The spring should be mounted so that chips and coolant flow from the largest diameter towards the smallest diameter.

